

# ADAS Subroutine xx0000

SUBROUTINE XX0000

```
C-----
C
C ***** FORTRAN77 SUBROUTINE: XX0000 *****
C
C PURPOSE: ADAS CONFIGURATION FILE FOR SETTING MACHINE DEPENDANT
C           VARIABLES ETC.
C
C CALLING PROGRAM: ANY MAIN ADAS PROGRAM
C
C
C SUBROUTINE:
C
C           (I*4)  I4UNIT  = FUNCTION (SEE ROUTINE SECTION BELOW)
C           (I*4)  IDUMP   = GENERAL USE
C
C NOTE:
C
C
C ROUTINES:
C           ROUTINE      SOURCE      BRIEF DESCRIPTION
C           -----
C           I4UNIT       ADAS        SET UNIT NUMBER FOR OUTPUT OF MESSAGES
C
C
C AUTHOR:  PAUL E. BRIDEN (TESSELLA SUPPORT SERVICES PLC)
C          K1/0/37
C          JET EXT. 5023
C
C DATE:    23/04/93
C
C MODIFIED: 6/3/94 L. JALOTA  CHANGED OUTPUT UNIT TO 0 FOR
C ERROR MESSAGES SO AS NOT TO
C INTERFERE WITH POIPE COMMUN-
C ICATIONS WITH IDL.
C-----
C-----
```