

ADAS Subroutine xxmcpy

SUBROUTINE XXMCPY(NR , NC , A , B)

C

C

C-----

C

C ***** FORTRAN77 SUBROUTINE: XXVADD *****

C

C PURPOSE: COPIES ONE MATRIX TO ANOTHER.

C

C CALLING PROGRAM: GENERAL USE.

C

C INPUT : (I*4) NR = NUMBER OF ROWS IN MATRICES 'A' AND 'B'.

C INPUT : (I*4) NC = NUMBER OF COLUMNS IN MATRICES 'A' AND 'B'.

C INPUT : (R*8) A(,) = INPUT MATRIX.

C 1ST DIMENSION: NR

C 2ND DIMENSION: NC

C

C OUTPUT: (R*8) B(,) = OUTPUT MATRIX.

C 1ST DIMENSION: NR

C 2ND DIMENSION: NC

C

C (I*4) I = LOOP INDEX.

C (I*4) J = LOOP INDEX.

C

C ROUTINES: NONE

C

C AUTHOR: JONATHAN NASH (TESSELLA SUPPORT SERVICES PLC)

C K1/0/81

C JET EXT. 5183

C

C DATE: 11/11/93

C

C UNIX-IDL PORT:

C

C AUTHOR: WILLIAM OSBORN (TESSELLA SUPPORT SERVICES PLC)

C

C DATE: 22ND MAY 1996

C

C VERSION: 1.1 DATE: 22-05-96

C MODIFIED: WILLIAM OSBORN

C - FIRST VERSION. IBM VERSION NOT CHANGED

C

C-----

C

C-----

INTEGER NC, NR
REAL*8 A(NR,NC), B(NR,NC)